

Square Straight Steel Pole

High-Strength Steel Tube, Galvanized Inside & Out

10–30 FT

A — POLE SHAFT

Built from high-strength steel tube, galvanized inside and out, and standard side-drilled for arm mount. Conforms to ASTM A500 Grade B, minimum yield strength 46,000 psi. Backed by a 5-year warranty. Available in five standard heights below; each height ships with the matching base size and bolt circle shown. Add a “-BNZ” or “-BK” suffix to the code when ordering to specify Bronze or Black finish.

SPECIFICATION TYPE	HEIGHT	WALL THICKNESS	SHAFT BASE	BASE SIZE	BOLT CIRCLE (IN)	BOLT PROJECTION
10FT4-D-T	10 Ft	11 Gauge	4x4 in	11 in	8.27" - 11.42"	2.75 in
15FT4-D-T	15 Ft	11 Gauge	4x4 in	11 in	8.27" - 11.42"	2.75 in
20FT4-11GA	20 Ft	11 Gauge	4x4 in	11 in	8.27" - 11.42"	2.75 in
25FT4-11GA	25 Ft	11 Gauge	4x4 in	11 in	8.27" - 11.42"	2.75 in
30FT5-11GA	30 Ft	11 Gauge	5x5 in	11 in	9.86" - 11.42"	2.75 in

B — MOUNTING OPTIONS

10FT & 15FT POLES	20FT, 25FT & 30FT POLES (PMPF MODELS)
Standard side-drilled for arm mount. Tenon top included standard. Note: additional installation parts (such as a pole cap) may be required when using arm or slip-fitter mounts.	All poles drilled at 90° for side-mounting hardware. Ships standard with a rubber-fitted cap / rain guard and hole plugs for unused mounting holes, plus a pole cap. If tenon installation is needed, VT4 and VT5 tenon adapters are available separately.

C — FINISH & HAND HOLE

FINISH TYPE	Textured architectural powder coat, baked for maximum adhesion & durability
AVAILABLE COLORS	Bronze or Black
HAND HOLE	3" x 5" cover with waterproof gasket
WARRANTY	5-year manufacturer warranty

D — FOUNDATION & ANCHOR BOLTS

Recommended foundation size by pole height (L x W x H). Anchor bolt hardware differs between the 10–25' range and the 30' pole — confirm the correct anchor bolt positioning plate and bolt length for your specific pole height before pouring the foundation.

POLE HEIGHT	L	W	H	ANCHOR BOLT
10–15 FT	19.69"	19.69"	23.62"	M0.79", 3.15" projection
20–25 FT	23.62"	23.62"	27.56"	M0.79", 3.15" projection
30 FT	27.56"	27.56"	39.37"	M0.95", 36" length

ORDERING INFORMATION

Reference the Specification Type code from the pole size table above and add a color suffix. **Example: 20FT4-11GA-BNZ (Bronze) or 20FT4-11GA-BK (Black)**

SPEC TYPE CODE	HEIGHT	SHAFT BASE	GAUGE	COLOR
See table above	10–30'	4x4 or 5x5 in	11 ga.	Bronze (BNZ) or Black (BK)

INCLUDED & ACCESSORIES

INCLUDED STANDARD	ACCESSORIES (SOLD SEPARATELY)
• J-bolts, set plate, nuts & washers • Base cover • Tenon top (10ft & 15ft poles) • Pole cap (20ft, 25ft & 30ft poles) • Rubber cap / rain guard & hole plugs (20–30ft PMPF models)	• VT4 tenon adapter • VT5 tenon adapter (for tenon installation on 20ft, 25ft & 30ft PMPF poles)