

Round Straight Steel Pole

High-Strength Steel Tube, Galvanized Inside & Out

10–30 FT

A — POLE SHAFT

Built from high-strength steel tube, galvanized inside and out, standard side-drilled for arm mount, and includes a tenon mount. Conforms to ASTM A500 Grade B, minimum yield strength 46,000 psi. Backed by a 5-year warranty. Available in five standard heights below. Add a “-BNZ” or “-BK” suffix to the code when ordering to specify Bronze or Black finish.

SPECIFICATION	HEIGHT	WALL THICKNESS	SHAFT BASE	WEIGHT (LBS)
R10FT3-11G-D	10 Ft	11 Gauge	3" dia	72
R15FT4-11G-D	15 Ft	11 Gauge	4" dia	95
R20FT4-11G-D	20 Ft	11 Gauge	4" dia	149
R25FT4-11G-D	25 Ft	11 Gauge	4" dia	176
R30FT5-11G-D	30 Ft	11 Gauge	5" dia	242

B — MOUNTING OPTIONS

SIDE MOUNT (STANDARD)	TOP MOUNT (OPTIONAL)
Standard length poles are predrilled (2 @ 180°), with a polycarbonate top cover and hole plugs for unused predrilled locations. Note: additional installation parts may be required when using arm or slip-fitter mounts.	Round Pole Tenon Adapters can be installed for use with a slip-fitter or multi-fixture installation requiring bullhorns, spokes, etc. Available in 3" RND, 4" RND, and 5" RND to 2-3/8" round tenon adapters.

C — FINISH & HAND HOLE

FINISH TYPE	Textured architectural powder coat, baked for maximum adhesion & durability
AVAILABLE COLORS	Bronze or Black
HAND HOLE	Cast iron reinforced hand hole and cover with ground screw (3" x 5" opening)
BASE COVER	Two-piece formed steel base cover, field-assembled over the pole base
ANCHOR BOLTS	Included standard
WARRANTY	5-year manufacturer warranty

D — FOUNDATION & ANCHOR BOLTS

Recommended cylindrical foundation size by pole height (diameter x height). Anchor bolt hardware differs between the 10–25' range and the 30' pole — confirm the correct anchor bolt positioning plate and bolt length for your specific pole height before pouring the foundation. Foundation sizing is a general reference only; actual requirements vary by local soil conditions.

POLE HEIGHT	DIAMETER	HEIGHT	ANCHOR BOLT
10–15 FT	31.5"	59.1"	M0.79", 3.15" projection
20–25 FT	35.4"	70.9"	M0.79", 3.15" projection
30 FT	35.4"	82.7"	M0.95", 36" length

ORDERING INFORMATION

Reference the Specification code from the pole size table above and add a color suffix. **Example: R20FT4-11G-D-BNZ (Bronze) or R20FT4-11G-D-BK (Black)**

SPEC CODE	HEIGHT	SHAFT BASE	GAUGE	COLOR
See table above	10–30'	3" to 5" dia.	11 ga.	Bronze (BNZ) or Black (BK)

INCLUDED & ACCESSORIES

INCLUDED STANDARD	ACCESSORIES (SOLD SEPARATELY)
• Anchor bolts • Two-piece formed steel base cover • Tenon mount • Polycarbonate top cover & hole plugs (side-mount poles) • Cast iron hand hole cover with ground screw	• 3" RND to 2-3/8" round tenon adapter • 4" RND to 2-3/8" round tenon adapter • 5" RND to 2-3/8" round tenon adapter (for slip-fitter or multi-fixture installations requiring bullhorns or spokes)